



Natural Cork Underlayment Sheets

72001Q

CRACK SUPPRESSION

Acts as a crack isolation membrane that resists transfer of stress cracks from subfloor through to flooring surfaces

INSULATING

Reduces thermal transmission, increasing effectiveness of floor heating systems

SOUND ABSORBING

Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below

IIC STC Δ
71* | 62* | 24

*Ceramic tile on a 8" concrete slab with a suspended ceiling

NATURAL BARRIER

Cork is antimicrobial, mold and mildew resistant

EASY TO INSTALL

In both glue-down and loose lay configurations

VERSATILE

For use under ceramic tile, stone, marble, glued wood flooring and floating floor systems



ITEM #	DESCRIPTION	QTY	SIZE	COVERAGE
72001Q	1/2" (12 mm) Sheets	25 sheets	2' x 3'	150 sq. ft./case



Our Natural Cork products may contribute towards satisfying credits under the LEED® Green Building Program in the following areas:

- MR 4.1 - 5% Recycled Content of total building materials (post consumer + 1/2 of post industrial)
- MR 4.2 - 10% Recycled Content of total building materials (post consumer + 1/2 of post industrial)
- MR 6 - Specifying rapidly renewable building materials for 5% of total building materials.
- EQ 4.1 - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)