70-195 AquaBar "B" Moisture Vapor Retarder

FEATURES & BENEFITS:

- Meets CA01350 Indoor Air Quality Standards
- Cleavage Membrane ANSI A108.01 and A108.02
- Class II Vapor Retarder IRC, IBC and NWFA
- Federal Specification:
- UU-B-79a, Type 1, Grade "B", Style 1a
- ASTM D-779, ASTM D-828 and ASTM E-96

LESS MESS Clean and easy installation

AQUABAR

SPECIFICATIONS

WIDTH OF ROLL:

LENGTH OF ROLL:

WEIGHT PER ROLL:

COVERAGE:

VERSATILE

Use beneath wood flooring, ceramic tile and stone veneer or as a membrane on walls, counter tops, and residential showers

500 sq. ft./roll

36 in.

167 ft.

15 lbs.

PROTECTS

Slows moisture migration, prevents flooring from buckling, cupping or cracking

Aquabar "B" floor underlayment is an extremely effective moisture vapor retarder for use in a variety of interior construction applications. Consisting of two layers of asphalt laminated kraft paper, this product is a non-reinforced 30/30/30 duplex type Grade "B" paper. Aquabar "B" also acts as a 'slipsheet' to minimize dust and reduce noise.



made in

Fortifiber Building Systems Group[®] Protecting Your World from the Elements[®]

www.QEP.com

The Brand that Stands for Excellence.

U.S. Headquarters 866 435 8665

Canada 800 840 9422

Wood Flooring

Vapo

Aquabar "B"

Moisture

Europe/Middle East 0031 24 6485348 Australia 011 61 3 9797 1888

New Zealand 64 9 415 9700

.12816-7875