



72001Q/72005Q

Natural Cork Underlayment Sheets

For ceramic tile, stone, marble, glued wood flooring and floating floor systems

FEATURES & BENEFITS:

- Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below
- Use under ceramic tile, stone, marble, glued wood flooring and floating floor systems
- Acts as a crack isolation membrane that resists transfer of stress cracks from subfloor through to flooring surfaces
- Reduces thermal transmission, increasing the effectiveness of floor heating systems
- Easy to install in both glue-down and loosely configurations*



Our Natural Cork products may contribute towards satisfying credits under the LEED® Green Building Program in the following areas:

MR 4.1 - 5% Recycled Content of total building materials (post consumer + 1/2 of post industrial)

MR 4.2 - 10% Recycled Content of total building materials (post consumer + 1/2 of post industrial)

MR 6 - Specifying rapidly renewable building materials for 5% of total building materials.

EQ 4.1 - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)

2' x 3' Cork Underlayment Sheets	R-Value**	Acoustical Performance	IIC	STC
72005Q - 6 mm (1/4")				
Quantity: 5 sheets/case	0.74	With 6" cement slab	51	52
Coverage: 30 ft ² /case		With 6" cement slab & suspended ceiling	61	60
72001Q - 12 mm (1/2")				
Quantity: 25 sheets/case				
Coverage: 150 ft ² /case				

* For a list of recommended adhesives to use for glue-down installations, please go to www.qep.com or call 866-435-8665.

** R-Value - Rating used to measure resistance to heat flow.

Y2016-10136

The Brand that Stands for Excellence.

www.QEP.com

U.S. Headquarters
866 435 8665

Canada
800 840 9422

Europe/Middle East
0031 24 6485348

Australia
011 61 3 9797 1888

New Zealand
64 9 415 9700